



SOIL TEST EQUIPMENTS
PRODUCT BROCHURE

AUTOMATIC DIRECT RESIDUAL SHEAR MACHINE

S4180



**PRODUCT MODEL**

S4180	Automatic Direct / Residual Shear Test Machine, 220-240 V 50-60 Hz
S4180/110	Automatic Direct / Residual Shear Test Machine, 110 V 60 Hz
S4180/01	Direct / Residual Shear Test Frame
G345/S5	Load Cell, 5 Kn
G340/01	Linear Potentiometric Displacement Transducer (10x0.001 mm)
G340/02	Linear Potentiometric Displacement Transducer (25x0.001 mm)
S4180/05	Digital Readout Unit and Software for Direct / Residual Shear

STANDARDS

Standards	TS 1900-2 ASTM D3080 BS 1377-7 AASHTO T236 NF P094 071-1/2
-----------	--

INFORMATION

Manufacturer	TESTMACLAB LABORATUVAR TEST CİHAZLARI PAZ. VE DİŞ TİC. LTD. ŞTİ
Country of Origin	TÜRKİYE
Product name	Automatic Direct Residual Shear Test Machine

DESCRIPTION

The Testmak S4180 Automatic Direct Residual Shear Machine is capable of performing the consolidation and shearing phases of a standard direct shear and residual shear test under full automatic control.

The system consists of a computer-controlled unit that utilizes micro-stepper motors to apply the vertical and horizontal loads to the soil specimen. The system is capable of doing a consolidation process at 32 phase automatically.

Horizontal shearing can be applied at a specified rate of deformation or at a specified rate of horizontal force change, or at a specified set of force steps of a specified duration.

The system is capable of displaying the current status of a test and graphically portraying the progress of the test in real time. The system includes the capability for the operator to alter the test process and conditions at any stage of the test.

The Automatic Direct Residual Shear Test Machine is supplied complete with;

Load Cell 5 kN

Linear Potentiometric Displacement Transducer (10x0.001 mm)

Linear Potentiometric Displacement Transducer (25x0.001 mm)

Software

Shearbox Assemblies,

Slotted Weight Set

Other optional accessories including cutting ring and extrusion dolly should be ordered separately

ACCESSORIES FOR DIRECT RESIDUAL SHEAR MACHINE (Should be ordered separately)

- S4182 Shear Box Assembly, 60x60 mm
- S4182/01 Specimen Cutter, 60x60 mm
- S4182/02 Extrusion Dolly, 60x60 mm
- S4183 Shear Box Assembly, Ø 60 mm
- S4183/01 Specimen Cutter, Ø 60 mm
- S4183/02 Extrusion Dolly, Ø 60 mm
- S4184 Shear Box Assembly, 100x100 mm
- S4184/01 Specimen Cutter, 100x100 mm
- S4184/02 Extrusion Dolly, 100x100 mm
- S4185 Shear Box Assembly, Ø 100 mm
- S4185/01 Specimen Cutter, Ø 100 mm
- S4185/02 Extrusion Dolly, Ø 100 mm
- S4186 Shear Box Assembly, Ø 2.5 inch
- S4186/01 Specimen Cutter, Ø 2.5 inch
- S4186/02 Extrusion Dolly, Ø 2.5 inch
- S4180/W50 Slotted Weight Set, 50 kg (4x10 kg + 1x5 kg + 2x2 kg + 1x1 kg)

TECHNICAL SPECIFICATIONS

Product Code	S4180
Maximum Shear Force	5 kN (5000 N)
Speed Range	0.00001 to 10,00 mm/min
Horizontal Travel	30 mm
Maximum Vertical Load	0 to 500 N
Dimensions	500x1250x1250 mm
Weight	120 kg
Power	1100 W

THANK YOU

FOR CHOOSE US

Dear business partners, thank you very much for believing in us and recommending our products to your customers; We sincerely believe that our company will grow even more thanks to you, our esteemed business partners.

You can reach us than our phones or e mail address 24 hours a day.

CONTACT US



Ağaç Metal Sanayi Sitesi 1354 Cadde
1436 Sokak No:16 İvogsan Yenimahalle -
ANKARA / TÜRKİYE



info@testmak.com
marketing@testmak.com



TÜRKİYE / HEAD Office : +90 312 395 44 57
UKRAINE Office : +380 63 741 29 20
SOUTH AMERICA / Cuba Office : +53 5 073 96 12



www.testmak.com