

Modified Proctor Moulds and Rammers



SOIL

Modified Proctor Moulds and Rammers



PRODUCT MODEL

MODIFIED PROCTOR MOULDS

S4435/A	Modified Proctor Mould ASTM Standards
S4435/E	B Type Modified Proctor Mould EN Standards
S4435/B	Modified Proctor Mould BS Standards

MODIFIED PROCTOR RAMMERS

S4440/A	Modified Proctor Rammer ASTM Standards
S4440/E	B Type Modified Rammer Mould EN Standards
S4440/B	4,5 kg Modified Proctor Rammer BS Standards

STANDARDS

Standards	ASTM D 698 , D 1557, D 558 AASHTO T 99, T180, T 134 EN 12386-2, 13286-4 BS 1377:4,1924:2
-----------	--

INFORMATION

Manufacturer	TESTMAK INS.LAB.MAK.SAN.VE TIC. PAZ. İTH. İHR. LTD. STİ
Country of Origin	TURKEY
Product Name	Modified Proctor Moulds and Rammers

Modified Proctor Moulds and Rammers

DESCRIPTION

Modified Moulds are used for determining the moisture content and density of compacted soil. These are made of plated steel for corrosion, includes collar, mould body and base plate. Modified Proctor Rammers are used to compact the soil sample in the Proctor. Different models are available conforming to the international standards.

TECHNICAL SPECIFICATIONS

P.Code	Product Name	Internal Dia.	Body	Volume	Weight
S4435/A	Modified Proctor Mould ASTM Standards	152.4 ± 0.7 mm	116.4 ± 0.5 mm	2124 ± 25 cm ³	9 kg
S4435/E	B Type Modified Proctor Mould EN Standards	150 ± 1 mm	120 ± 1 mm	2120 cm ³	8.9 kg
S4435/B	Modified Proctor Mould BS Standards	152 ± 0.5 mm	127 ± 1 mm	2.303 cm ³	7.3 kg
P.Code	Product Name	Internal Dia.	Body	Volume	Weight
S4440/A	Modified Proctor Rammer ASTM Standards	50.8 mm	457 ± 1.3 mm	4540 ± 10 g	8 kg
S4440/E	B Type Modified Rammer Mould EN Standards	50 ± 0.5 mm	457 ± 3 mm	4500 ± 40 g	8 kg
S4440/B	4,5 kg Modified Proctor Rammer BS Standards	50 ± 0.5 mm	450 ± 4 mm	4500 ± 50 g	8 kg





Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY