

**Air Entrainment
Meter**



CONCRETE

Air Entrainment Meter



PRODUCT MODEL

TMC-3210	Air Entrainment Meter
TMC-3212	Manometer for TMC-3210
TMC-3564	Tamping Rod Ø16x600 mm
TMS-4482	Straight Edge 300x30x3 mm

STANDARDS

EN 12350-7 | ASTM C231 | AASHTO T152

INFORMATION

Manufacturer	: TESTMAK INS.LAB.MAK.SAN.VE TİC. PAZ. İTH. İHR. LTD. STİ
Country of Origin	: TURKEY
Product Name	: Air Entrainment Meter
Code of Product	: TMC-3210

Air Entrainment Meter

DESCRIPTION

The Testmak TMC-3210 series Air Entrainment Meter is produced for the determination of air content of compacted fresh concrete. The primary purpose of air entrainment is to increase the durability of the hardened concrete. Air Entrainment Meter measures up to 22% entrained air with an accuracy of $\pm 0.25\%$ at full scale. The Air Meter is can be calibrated. This instrument is 7 liter capacity and it is supplied complete with pump, manometer, tamping rod and straight edge.

The Air Entrainment Meter is supplied complete with;

- Straight Edge
- Tamping Rod
- Wash Bottle. 250cc
- J-Type pipe and an inner extension pipe for calibration
- Carrying Case

TECHNICAL SPECIFICATIONS

Capacity	7 Liters
Air Content Range	0 - 10%
Graduations	0.1% up to 6%; 0.2% from 6 to 10%
Dimensions	320x320x650 mm
Weight (approx.)	17 kg



Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY