



**Core Drilling
Machine**

CONCRETE

Core Drilling Machine



PRODUCT MODEL

TMC-3260	Core Drilling Machine, Coring Range 16-162 mm
TMC-3268	Core Drilling Machine, Coring Range 25-202 mm
TMC-3261	Coring Bit for Concrete 50 mm dia. x 400 mm length
TMC-3262	Coring Bit for Concrete 75 mm dia. x 400 mm length
TMC-3263	Coring Bit for Concrete 100 mm dia. x 400 mm length
TMC-3264	Coring Bit for Concrete 150 mm dia. x 400 mm length
TMC-3265	Coring Bit for Concrete 200 mm dia. x 400 mm length

STANDARDS

General

INFORMATION

Manufacturer : TESTMAK INS.LAB.MAK.SAN.VE TİC. PAZ. İTH. İHR. LTD. STİ
Country of Origin : TURKEY
Product Name : Core Drilling Machine
Code of Product : TMC-3260, 3268

Core Drilling Machine

DESCRIPTION

The TMC-3260 and TMC-3268 Core Drilling Machines are powerful diamond drilling units serve for shock free drilling into concrete, natural stone and asphalt with diameter ranges 16-162 mm and 25-202 mm for TMC-3260 and TMC-3268 respectively. Both models are optimal complements to handheld diamond drilling machines.

- Mechanical oil-bath gearbox with integrated oil pump for durable lubrication of the armature pinion
- Electronics- soft start, temperature control and over current cut off, optical overload indication, constant speed
- Quick- change plate for motor/ rig
- Shaft seals replaceable from the outside
- Cut-off carbon brushes to protect the motor
- Mechanical safety clutch

Core Drilling Machines are supplied complete with;

- Base Unit
- Motor Swivel Attachment
- Strap Wrench

TECHNICAL SPECIFICATIONS

P. Code	TMC-3260	TMC-3268
Power	1600 W	2200 W
Class of Protection	I	I
Drilling Diameter	16-162 mm	25-202 mm
No-Load Speed	650/1380 r.p.m.	420/700/1570 r.p.m.
Gearbox	2-speed/oil bath	3-speed/oil bath
Dimensions	500x300x1150 mm	500x300x1150 mm
Weight (approx.)	18 kg	20 kg



TM TEST MAK
MATERIAL TEST EQUIPMENTS

Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY