

Water Baths



ASPHALT

Water Baths



PRODUCT MODEL

E9600/15	Water Bath, 15 L, 220-240V 50/60 Hz
E9600/24	Water Bath, 24 L, 220-240V 50/60 Hz
E9600/30	Water Bath, 30 L, 220-240V 50/60 Hz
E9600/48	Water Bath, 48 L, 220-240V 50/60 Hz
E9600/56	Water Bath, 56 L, 220-240V 50/60 Hz
E9600/10CS	Water Bath with Cooler Unit, 15 L, 220-240V 50/60 Hz
E9600/24CS	Water Bath with Cooler Unit, 24 L, 220-240V 50/60 Hz
E9600/30CS	Water Bath with Cooler Unit, 30 L, 220-240V 50/60 Hz
E9600/48CS	Water Bath with Cooler Unit, 48 L, 220-240V 50/60 Hz

PRODUCT STANDARDS

Standards | ASTM D1559 | EN 12697-34 | EN 13108th | D5581 | AASHTO T245

INFORMATION

Manufacturer	TESTMAK INS.LAB.MAK.SAN.VE TİC. PAZ. İTH. İHR. LTD. STİ
Country of Origin	TURKEY
Product name	Water Baths

Water Baths

DESCRIPTION

Testmak Series Water Baths are used in various material testing analyses. 15, 24, 30, 48 and 56 lt. tank capacity models are available and can be ordered with or without cooler units. Temperature is from ambient to 95°C. Internal surfaces are polished stainless steel with a sheet steel insulated outercase.

The EN 12697-23 covering the determination of the strength of bituminous mixtures, prescribe a water conditioning temperature of 5°C or from 5 to 25°C which are obtainable with a cooling system. Water bath are used for asphalt (marshall, bitumen testing), cement (curing on conditioning) applications. The cooler unit is located under the water bath. Complete with re-circulating unit for temperature uniformity.

TECHNICAL SPECIFICATIONS

P. Code	Internal Dimensions	External Dimensions	Weight (kg)	Temperature Range
E9600/15	160x380x250 mm	300x580x350 mm	15 kg	for ambient to +90°C ± 1°C
E9600/24	160x520x300 mm	300x720x400 mm	18 kg	for ambient to +90°C ± 1°C
E9600/30	160x520x370 mm	300x720x470 mm	20 kg	for ambient to +90°C ± 1°C
E9600/48	160x620x500 mm	300x820x600 mm	25 kg	for ambient to +90°C ± 1°C
E9600/56	160x650x540 mm	300x820x600 mm	30 kg	for ambient to +90°C ± 1°C
E9600/10CS	160x380x250 mm	300x720x600 mm	26 kg	+5°C to +70°C± 0,5°C
E9600/24CS	160x520x300 mm	300x720x700 mm	29 kg	+5°C to +70°C± 0,5°C
E9600/30CS	160x520x370 mm	300x720x760 mm	32 kg	+5°C to +70°C± 0,5°C
E9600/48CS	160x620x500 mm	300x820x900 mm	48 kg	+5°C to +70°C± 0,5°C



TM TEST MAK
MATERIAL TEST EQUIPMENTS

Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY