

**SAND EQUIVALENT SHAKER
WITH
SAFETY COVER**



AGGREGATE

Sand Equivalent Shaker with Safety Cover



PRODUCT MODEL

AG1475/A	Sand Equivalent Shaker with Safety Cover, ASTM - 220 V 50/60 Hz
AG1475/E	Sand Equivalent Shaker with Safety Cover, EN - 220 V 50/60 Hz
AG1475/A-110	Sand Equivalent Shaker with Safety Cover ASTM - 110 V 60 Hz

PRODUCT STANDARDS

Standards EN 933-8 | ASTM D2419 | AASHTO T176 | UNI 7446

INFORMATION

Manufacturer	TESTMAK INS.LAB.MAK.SAN.VE TIC. PAZ. ITH. IHR. LTD. STI
Country of Origin	TURKEY
Product name	Sand Equivalent Shaker

Sand Equivalent Shaker with Safety Cover

DESCRIPTION

The AG1475/A and AG1475/E Sand Equivalent Shaker (With Safety Cabin) is used for the uniform shaking of sand equivalent measuring cylinders, at a specified rate and stroke. On the shaker has a timer and safety cover (conforming with CE directives). The horizontal movement, cycle and shaking time can be adjusted on the shaker to comply with EN or ASTM standards.

Sand Equivalent Shaker ASTM Model

The Sand equivalent shaker with a stroke of 203 mm (8 inches) and a running frequency of 175 ± 2 cycles per minute for ASTM Model. The digital timer stops shaker upon test completion.

Sand Equivalent Shaker EN Model

The Sand equivalent shaker with a stroke of $200 \text{ mm} \pm 10 \text{ mm}$ and a running frequency of 180 ± 3 cycles per minute for ASTM Model. The digital timer stops shaker upon test completion.

TECHNICAL SPECIFICATIONS

Standard	ASTM	EN
Horizontal Movement	203.2 mm \pm 1 mm	200 mm \pm 10 mm
Cycle	175 \pm 2 / min.	180 \pm 3 / min
Dimensions	700x360x450mm	700x360x450mm
Weight (approx)	52 kg	52 kg
Power	200 W	200 W



TESTMAK
MATERIAL TEST EQUIPMENTS

Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY