



**Solvent Recovery Distiller  
Unit**

**ASPHALT**

## Solvent Recovery Distiller Unit



### PRODUCT MODEL

B1810	Solvent Recovery Distiller Unit, 220-240 V 50-60 Hz
B1810/110	Solvent Recovery Distiller Unit, 110 V 60 Hz

### INFORMATION

Manufacturer	TESTMAK INS.LAB.MAK.SAN.VE TİC. PAZ. İTH. İHR. LTD. STİ
Country of Origin	TURKEY
Product name	Solvent Recovery Distiller Unit

## Solvent Recovery Distiller Unit

### DESCRIPTION

The Solvent Recovery Distiller Unit is used to recover the solvent liquid after its use for the extraction tests. This recovery unit has been designed to recover unflammable solvents. The consists of two stainless steel chambers. The first chamber is used for dirty solvent. The second chamber used for cleaned solvent. A Solvent in the left-hand side chamber is distilled by an electrical heater and then passes through a water cooling system and drops into the second chamber ready for re-use a test. Once the process is completed, a temperature switch automatically stops the heating elements. The solvent recovery unit is supplied complete with 10 m plastic tubing, tube clamps, sieve insert 0.6 mm opening and one lid.

**The Solvent Recovery Unit is supplied complete with;**

- Plastic Tubing, 10 m
- Tube Clamps
- Sieve Insert, 0.6 mm
- Lid

### TECHNICAL SPECIFICATIONS

Product Code	B1810
Max. Temperature	150°C
Dimensions	420x350x680 mm
Weight (approx)	20 kg
Power	1200 W



**TM TEST MAK**  
**MATERIAL TEST EQUIPMENTS**

Telephone : +90 312 395 36 42  
Fax : +90 312 395 36 01

Website : [www.testmak.com](http://www.testmak.com)  
E-Mail : [info@testmak.com](mailto:info@testmak.com)

Koca Sinan Industrial Sites 1183 Street No:  
40 06370 OSTIM / ANKARA / TURKEY