



**SPEEDY MOISTURE
TEST DEVICE**



AGGREGATE

www.testmak.com

Speedy Moisture Test Device



PRODUCT MODEL

AG1400 Speedy Moisture Test Device

PRODUCT STANDARDS

Standards BS 812-109

INFORMATION

Manufacturer	TESTMAK INS.LAB.MAK.SAN.VE TIC. PAZ. İTH. İHR. LTD. STİ
Country of Origin	TURKEY
Product name	Speedy Moisture Test Device

Speedy Moisture Test Device

DESCRIPTION

The Speedy moisture device is field conditions dust, pulp mixture and the soil, sand, clay, aggregate and other granular materials quickly and accurately detect moisture content. Moisture within the sample, as a result of reaction with calcium carbide acetylene gas occurs. The resulting pressure caused by gas, dial indicator is determined as the percent moisture content. Within a few minutes into the issue determines the moisture content of the sample. Precision Scale, measuring spoons and cups, calibration kit, 1 box of calcium carbide reagent, cleaning brush, wooden enclosure with a complete set as.

- 20 cup capacity
- Humidity Range: 0 - 20%
- Net Weight: 8 Kg

TECHNICAL SPECIFICATIONS

Technical Specifications	
Dimensions	700x500x300 mm
Weight (approx.)	8 kg



TM TEST MAK
MATERIAL TEST EQUIPMENTS

Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY