



Ductility Testing Machine



ASPHALT

www.testmak.com

Ductility Testing Machine

DESCRIPTION

The Testmak Ductility Testing Machines determine ductility of formed asphalt or semi-solid bitumen by measuring the distance of elongation before reaching the breaking point of a briquette sample, which is pulled apart at a specific speed and temperature. The Internal tank is made of stainless steel. The bath is fitted with an immersion heater in order to obtain, the 25°C test temperature. Suitable for testing 3 samples simultaneously. Standard carriage stroke is 1500 mm. The machine consist of graduated scale, moulds and mould base plates. The ductility machine comprises speed control and water circulator to maintain the homogeneous water temperature.

The B1652 Ductility Testing Machine with Cooling Unit has the same specifications with B1650 Ductility Testing Machine but with an additional cooling unit and It is not possible to convert B1650 to B1652.

TECHNICAL SPECIFICATIONS

Speed	50 mm/min.
Carriage Stroke	1500 mm
Dimensions	320x1800x600 mm
Weight (approx)	90 kg
Power	350 W



TESTMAK
MATERIAL TEST EQUIPMENTS

Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY