

## Cement Flow Table



**CEMENT**

## Cement Flow Table



### PRODUCT MODEL

M2520/A	Manual Cement Flow Table ASTM Standards
M2525/A	Motorized Cement Flow Table ASTM Standards, 220-240 V 50 Hz
M2520/E	Manual Cement Flow Table EN Standards
M2525/E	Motorized Cement Flow Table EN Standards, 220-240 V 50 Hz
M2520/01	Tamper EN Ø 40x200 mm 250 gr
M2520/02	Brass Mould EN - 100 mm base dia. x 70 mm top dia. x 60 mm height
M2520/03	Tamper ASTM Hardwood 13x25x150 mm
M2520/04	Brass Mould ASTM - 100 mm base dia. x 70 mm top dia. x 50 mm height

### PRODUCT STANDARDS

Standards | ASTM C230 | EN 459-2, 1015-3

### INFORMATION

Manufacturer	TESTMAK INS.LAB.MAK.SAN.VE TİC. PAZ. İTH. İHR. LTD. STİ
Country of Origin	TURKEY
Product name	Cement Flow Tables

## Cement Flow Table

### DESCRIPTION

The Cement Flow Tables are used for determining the consistency of mortar, lime and cement specimens. Cement Flow Table are produced in two models as manual and motorized.

The M2520/A and M2520/E manual models cement flow tables are included with a hand wheel. The M2525/A and M2525/E motor operated models cement flow tables are driven by a motor speed reducer coupling at the rate of one rev per second. The number of drops can preset on a counter and the machine stops automatically at the end of the cycle.

**Cement Flow Tables consists of the following equipment;**

- Bronze Flow Mould,
- Filling Hopper and Tamper.

### TECHNICAL SPECIFICATIONS

	M2520/A & M2525/A	M2520/E & M2525/E
Table Dia.	254 mm	300 mm
Cone Top/Base Dia.	70 mm / 100 mm	70 mm / 100 mm
Cone Height	50 mm	60 mm
Drop Height	12.7 mm	10 mm

	M2520/A & M2520/E	M2525/A & M2525/E
Dimensions	270x270x280 mm	460x350x360 mm
Weight (kg)	14 kg	38 kg



**TM TEST MAK**  
**MATERIAL TEST EQUIPMENTS**

Telephone : +90 312 395 36 42  
Fax : +90 312 395 36 01

Website : [www.testmak.com](http://www.testmak.com)  
E-Mail : [info@testmak.com](mailto:info@testmak.com)

Koca Sinan Industrial Sites 1183 Street No:  
40 06370 OSTIM / ANKARA / TURKEY