



Flow Cone Apparatus

CEMENT

Flow Cone Apparatus



PRODUCT MODEL

M2580	Flow Cone Apparatus Test Set
M2580/01	Flow Cone
M2580/02	Nozzle Ø 8 mm
M2580/03	Nozzle Ø 9 mm
M2580/04	Nozzle Ø 10 mm
M2580/05	Nozzle Ø 11 mm
M2580/06	Nozzle Ø 13 mm

PRODUCT STANDARDS

Standards	EN 445 NF P18-358 NF P18-507
-----------	----------------------------------

INFORMATION

Manufacturer	TESTMAK INS.LAB.MAK.SAN.VE TİC. PAZ. İTH. İHR. LTD. STİ
Country of Origin	TURKEY
Product name	Flow Cone Apparatus Test Set

Flow Cone Apparatus

DESCRIPTION

The TESTMAK Flow Cone Apparatus is used for determining the flow properties of grouts, mortars, muds and other fluid materials. Flow Cone Apparatus consists of a stainless steel cone with upper diameter of 150 mm height of 280 mm, 150 mm dia sieve with 1.5 mm opening for the upper cone, 5 interchangeable (8, 9, 10, 11 and 13 mm diameter) nozzles with fitting bush and a 1 liter capacity cup.

The Flow Cone Apparatus Test Set is supplied complete with;

- Stand
- Flow Cone,
- Sieve 1,5 mm,
- Nozzle 8, 9, 10, 11 and 13 mm
- Cup 1 lt,
- Fitting Bush

TECHNICAL SPECIFICATIONS

P.Code	TMM-2580
Dimensions	250x250x590 mm
Weight	12 kg





TM TEST MAK
MATERIAL TEST EQUIPMENTS

Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY