



Muffle Furnaces

ASPHALT

Muffle Furnaces



PRODUCT MODEL

E1370/03	Muffle Furnace 3 Liters , 220-240 V 50-60 Hz
E1370/05	Muffle Furnace 5 Liters , 220-240 V 50-60 Hz
E1370/07	Muffle Furnace 7 Liters , 220-240 V 50-60 Hz

PRODUCT STANDARDS

Standards	TS EN 196-2 196-21 459-2
-----------	------------------------------

INFORMATION

Manufacturer	TESTMAK INS.LAB.MAK.SAN.VE TİC. PAZ. İTH. İHR. LTD. STİ
Country of Origin	TURKEY
Product name	Muffle Furnaces

Muffle Furnaces

DESCRIPTION

The Muffle Furnaces are used for determining various properties of construction materials, and they cover a temperature range from 1100°C to 1600°C, they are all front loading for easy operation and are of a double skin construction to maintain a cool outer case. Excellent temperature control is provided by a PID digital control system. A vertical counter balanced door keeps the hot insulation away from the operator which opens in an upward movement. The Furnace has a safety switch which isolates the power when the door is opened.

TECHNICAL SPECIFICATIONS

Product Code	E1370/03	E1370/05	E1370/07
Internal Volume	3 Liter	5 Liter	7 Liter
Max. Temperature	1100 °C	1100 °C	1600 °C
Max. Continuous Temperature	1000 °C	1000 °C	1550 °C
Temperature Deviation at Set Point	± 2°C	± 2°C	± 2°C
Heat Up Time to Max. Temperature	50 min.	50 min.	75 min.
Phase	1	1	3
Internal Dimensons (mm)	100x135x200 mm	140x180x200 mm	170x150x250 mm
External Dimensons (mm)	430x330x360 mm	660x550x590 mm	680x580x620 mm
Weight	24 kg	58 kg	70 kg
Power	2000 W	2000 W	4900 W



Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY