

**Slump Cone Test  
Set**



**CONCRETE**



## Slump Cone Test Set

### DESCRIPTION

The Slump Cone Test Set is used for the determination of the consistency and workability of fresh concrete. It is used, indirectly, as a means of checking that the correct amount of water has been added to the mix. The test is carried out in fresh concrete. The Slump Test Set is galvanized to prevent corrosion.

**The Slump Cone Test Set is supplied complete with**

- Slump Cone Top Dia: 100 ±2 mm / Base Dia: 200 ±2 mm / Height: 300 ±2 mm
- Slump Base Plate 500x500x60 mm with Handle
- Slump Funnel, Galvanized Steel
- Tamping Rod Ø 16x600 mm
- Rubber Mallet
- Steel Ruler 300x1 mm
- Round Scoop Medium
- Wire Brush with Handle

### TECHNICAL SPECIFICATIONS

P. Code	Dimensions(mm)	Weight (kg)
TMC-3560	550x600x250 mm	7 kg



**TM TEST MAK**  
**MATERIAL TEST EQUIPMENTS**

Telephone : +90 312 395 36 42  
Fax : +90 312 395 36 01

Website : [www.testmak.com](http://www.testmak.com)  
E-Mail : [info@testmak.com](mailto:info@testmak.com)

Koca Sinan Industrial Sites 1183 Street No:  
40 06370 OSTIM / ANKARA / TURKEY