

**Mortar Prism
Moulds**



CEMENT

Mortar Prism Moulds



PRODUCT MODEL

M2480	Cube Mould 70.7 mm, Steel, BS
M2490	Three Gang Cube Mould 50x50x50 mm, Steel, ASTM
M2500	Three Gang Mould 40x40x160 mm, Steel, EN
M2500/02	Feed Hopper 40x40x160 mm for M2500
M2500/03	Short and Long Spreaders and Straight Edge for M2500

PRODUCT STANDARDS

Standards EN 196-1 | ASTM C109 | BS 4550

INFORMATION

Manufacturer	TESTMAK INS.LAB.MAK.SAN.VE TİC. PAZ. İTH. İHR. LTD. STİ
Country of Origin	TURKEY
Product name	Mortar Prism Moulds

Mortar Prism Moulds

DESCRIPTION

Three Gang Mortar Prism Moulds are have been manufactured from steel and all internal surfaces are machined. Dimensions and specifications comply with the related standards. The moulds has the surface hardness of a minimum HV400.

TECHNICAL SPECIFICATIONS

P. Code	Dimensions(mm)	Weight (kg)
M2480	100x125x90 mm	3.5 kg
M2490	110x230x60 mm	3 kg
M2500	190x300x70 mm	12 kg





TM TEST MAK
MATERIAL TEST EQUIPMENTS

Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY