



Centrifuge Binder

Extractor

B1580



M

Centrifuge Binder Extractor



PRODUCT MODEL

B1580	Centrifuge Binder Extractor 3000 g, 220-240 V 50/60 Hz	
B1580/110	Centrifuge Binder Extractor 3000 g, 110 V 60 Hz	
B1580/01	Rotating Bowl and Cover for B1580 and B1580/110	
B1580/02	Filter Paper 295 mm Outer dia. 45 mm Inner dia. for B1580 and B1580/110 (100 pcs / Pack)	
B1585	Centrifuge Binder Extractor 1500 g, 220-240 V 50/60 Hz	
B1585/110	Centrifuge Binder Extractor 1500 g, 110 V 60 Hz	
B1585/01	Rotating Bowl and Cover for B1585 and B1585/110	
B1585/02	Filter Paper 250 mm Outer dia. 45 mm Inner dia. for B1585 and B1585/110(100 pcs / Pack)	

STANDARDS

Standards ASTM D2172 A | AASHTO T164-A | EN 12697-1 Clause B.1.5

INFORMATION

Manufacturer	TESTMACLAB LABORATUVAR TEST CİHAZLARI PAZ. VE DIŞ TİC. LTD. ŞTİ
Country of Origin	TÜRKİYE
Product name	Centrifuge Binder Extractor



Telephone: +90 312 395 44 57 Fax: +90 312 395 36 42 Website : www.testmak.com E-Mail : info@testmak.com Ağaç Metal Sanayi Sitesi 1354 Cadde 1436 Sokak No:16 Ivogsan Yenimahalle - ANKARA / TÜRKİYE

M

Centrifuge Binder Extractor

DESCRIPTION

The Centrifuge binder extractors are used for the determination of the bitumen percentage in bituminous mixtures. All models comprise a removable precision-machined rotor bowl housed in a cylindrical aluminum box. The bowl is driven by an electric motor fit with an AC drive (inverter) with the double function of speed control up to 3600 rpm regardless of the frequency (50 or 60 Hz) and electrical breaking. The centrifuge extractor can be set for the automatic speed ramp up to 3600 rpm and will stop in 10 seconds. The cover is precisely machined and fitted with a solvent resistant gasket to avoid leakages. All models are fit, for emergency use, by a hand brake system. The control panel includes: Start/Stop button and speed control knob. Digital display can added to monitor the rotational speed according to customer request. Two model available: Standard 1500 g (B1585) and 3000 g (B1580).

The Centrifuge Extractor is supplied with;

- · Bowl and Cover,
- Filter Paper 100 pcs.

TECHNICAL SPECIFICATIONS

Dimensions	550x400x500 mm
Weight (approx)	52 kg
Power	550 W

FILTER PAPER



B1580/02 | Filter Paper 295 mm Outer dia. 45 mm Inner dia. for TMB-1580 (100 pcs / Pack) B1585/02 | Filter Paper 250 mm Outer dia. 45 mm Inner dia. for TMB-1585 (100 pcs / Pack)



Telephone: +90 312 395 44 57 Fax: +90 312 395 36 42 Website: www.testmak.com E-Mail: info@testmak.com Ağaç Metal Sanayi Sitesi 1354 Cadde 1436 Sokak No:16 Ivogsan Yenimahalle - ANKARA / TÜRKİYE



THANK YOU

FOR CHOOSE US

Dear business partners, thank you very much for believing in us and recommending our products to your customers; We sincerely believe that our company will grow even more thanks to you, our esteemed business partners.

You can reach us than our phones or e mail address 24 hours a day.

CONTACT US



Ağaç Metal Sanayi Sitesi 1354 Cadde 1436 Sokak No:16 Ivogsan Yenimahalle -ANKARA / TÜRKİYE



info@testmak.com marketing@testmak.com



TÜRKİYE / HEAD Office : +90 312 395 44 57 UKRAINE Office : +380 63 741 29 20 SOUTH AMERICA / Cuba Office : +53 5 073 96 12



www.testmak.com