

**Standard Proctor
Moulds and Rammers**



SOIL

Standard Proctor Moulds and Rammers



PRODUCT MODEL

| STANDARD PROCTOR MOULDS | |
|--------------------------|---|
| S4445/A | Standard Proctor Mould ASTM Standards |
| S4445/E | A Type Standard Proctor Mould EN Standards |
| S4445/B | Standard Proctor Mould BS Standards |
| STANDARD PROCTOR RAMMERS | |
| S4450/A | Standard Proctor Rammer ASTM Standards |
| S4450/E | A Type Standard Rammer Mould EN Standards |
| S4450/B | 2,5 kg Standard Proctor Rammer BS Standards |

STANDARDS

| | |
|-----------|--|
| Standards | ASTM D 698 , D 1557, D 558 AASHTO T 99, T180, T 134 EN 12386-2, 13286-4 BS 1377:4,1924:2 |
|-----------|--|

INFORMATION

| | |
|-------------------|---|
| Manufacturer | TESTMAK INS.LAB.MAK.SAN.VE TIC. PAZ. ITH. IHR. LTD. STI |
| Country of Origin | TURKEY |
| Product Name | Standard Proctor Moulds and Rammers |

Standard Proctor Moulds and Rammers

DESCRIPTION

Standard Proctor Moulds are used for determining the moisture content and density of compacted soil. These are made of plated steel for corrosion, includes collar, mould body and base plate. Standard Proctor Rammers are used to compact the soil sample in the Proctor. Different models are available conforming to the international standards.

TECHNICAL SPECIFICATIONS

| P.Code | Product Name | Internal Dia. | Body | Volume | Weight |
|---------|---|----------------|----------------|--------------------------|--------|
| S4445/A | Standard Proctor Mould ASTM Standards | 101.6 ± 0.4 mm | 116.4 ± 0.5 mm | 944 ± 14 cm ³ | 6.8 kg |
| S4445/E | A Type Standard Proctor Mould EN Standards | 100 ± 1 mm | 120 ± 1 mm | 942 cm ³ | 5 kg |
| S4445/B | Standard Proctor Mould BS Standards | 105 ± 0.5 mm | 115,5± 0,5 mm | 1 cm ³ | 5.2 kg |
| P.Code | Product Name | Internal Dia. | Body | Volume | Weight |
| S4450/A | Standard Proctor Rammer ASTM Standards | 50.8 mm | 304.8± 1 mm | 2495 ± 23 g | 4.5 kg |
| S4450/E | A Type Standard Rammer Mould EN Standards | 50 ± 0.5 mm | 305± 3 mm | 2500 ± 20 g | 4.5 kg |
| S4450/B | 2,5 kg Standard Proctor Rammer BS Standards | 50 ± 0.5 mm | 300± 3 | 2500 ± 25 g | 4.5 kg |





TM TEST MAK
MATERIAL TEST EQUIPMENTS

Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY